



LECTROKLEEN - Q **NON-FLAMMABLE - VERY FAST EVAPORATING**

Description

LECTROKLEEN - Q is a non - flammable quick drying solvent, containing chlorinated hydrocarbons. LECTROKLEEN – Q has been specifically formulated to replace 1,1,1 Trichloroethane for all cleaning operations even for VAPOR DEGREASING.

Applications

LECTROKLEEN - Q is applied for cleaning and degreasing of electrical equipment such as motors, generators, switchgears, coils, etc. and as a general use cleaner for machine parts, equipment, motors, engines, etc. without the need for rinsing.

LECTROKLEEN - Q is alternatively used for vapor degreasing with excellent results.

Advantages

LECTROKLEEN - Q rapidly removes oil, grease, wax, dust, moisture, soil, etc. and has low toxicity, is not corrosive and evaporates leaving surfaces clean and dry.

High dielectric constant.(over 48.000 volts)

Specific resistance : 10^9 ohm.

Use

LECTROKLEEN - Q is used neat, by brush spray or swab.
Allow LECTROKLEEN - Q to completely evaporate leaving surface dry.

Specifications

Appearance:	Clear colorless liquid.
Flash point:	Non-flammable
Compatibility:	Safe for all metals.

Caution

LECTROKLEEN - Q contains chlorinated solvents. Avoid contact with skin and eyes. Do not inhale vapors. Use in ventilated areas. For further information refer to M.S.D.S.

Packaging

LECTROKLEEN - Q is offered in non - returnable 20 lt. pails, 210 lt. drums and 400 ml. aerosol cans.

-----...-----