



LECTROKLEEN - D4 - FAST **NON-FLAMMABLE**

Description

LECTROKLEEN - D4 - FAST is a non - flammable quick drying solvent, containing chlorinated hydrocarbons. LECTROKLEEN - D4 - FAST has been specifically formulated to replace 1,1,1 Trichloroethane for all cleaning operations even for VAPOR DEGREASING.

Applications

LECTROKLEEN - D4 - FAST is applied for cleaning and degreasing of electrical equipment such as motors, generators, switchgears, coils, etc. and as a general use cleaner for machine parts, equipment, motors, engines, etc. without the need for rinsing.

LECTROKLEEN - D4 - FAST is alternatively used for vapor degreasing with excellent results.

Advantages

LECTROKLEEN - D4 - FAST rapidly removes oil, grease, wax, dust, moisture, soil, etc. and has low toxicity, is not corrosive and evaporates leaving surfaces clean and dry.

High dielectric constant.(over 48.000 volts)
Specific resistance : 10^9 ohm.

Use

LECTROKLEEN - D4 - FAST is used neat, by brush spray or swab.
Allow LECTROKLEEN - D4 - FAST to completely evaporate leaving surface dry.

Specifications

Appearance:	Clear colorless liquid.
Flash point:	Non-flammable
Compatibility:	Safe for all metals.

Caution

LECTROKLEEN - D4 - FAST contains chlorinated solvents. Avoid contact with skin and eyes. Do not inhale vapors. Use in ventilated areas. For further information refer to M.S.D.S.

Packaging

LECTROKLEEN - D4 - FAST is offered in non - returnable 20 lt. pails, 210 lt. drums and 400 ml. aerosol cans.

-----,-----