



## **AC - 55** **WATER DILUTABLE** **EXTERIOR AIRCRAFT SURFACE CLEANER**

### **DESCRIPTION**

AC-55 is an alkaline water based compound, which meets the requirements of BOEING Document D6 – 17487, MIL-C-25769H and AMS-1526.

### **APPLICATION**

AC-55 is formulated to effectively clean painted and unpainted aircraft exterior surfaces. Removes dirt, grease, petroleum and synthetic oils, light carbon, etc. It is safe on all metals and well bonded paints.

Also does not attack plastic and Plexiglas when used according to instructions.

### **USAGE**

AC-55 can be applied by brush or spray. Normally AC-55 is used diluted 1 part up to 5-20 parts of water depending on the type and quantity of soil involved.

Allow to stand for approximately 5-15 minutes.

Brush all areas with stiff bristle brush and finally rinse with high-pressure water.

For extremely heavy soil AC-55 may be used neat or diluted 1 part up to 3 parts of water.

### **PRODUCT PROPERTIES**

Appearance:	Clear liquid
Boiling point:	100 °C
Solubility in water:	Complete in all proportions
Specific gravity:	1,020 ± 0,02 gr/cm <sup>3</sup>
PH (10 % sol):	11,5 ± 0,05
Flash point:	None to boil.

### **SAFETY**

AC-55 is an alkaline material. Avoid contact with skin and eyes. For further instructions refer to analytical Material Safety Data Sheet.

### **PACKAGING**

AC-55 is available in 210 Lt drums.