



KEM – 2015 – AP

THE MOST EFFECTIVE PAINT REMOVER

ACID ACTIVATED FOR AMINE-CURED EPOXY COATING SYSTEMS

Description

KEM-2015 AP is a viscous, acid activated, water rinsable, aircraft paint stripper, which meets the requirements of MIL-R-81903 TYPE II, class 1.

Application

KEM-2015 AP is especially designed for removing mainly polyurethane, epoxy paints and other highly resistant coatings where traditional paint removers have poor results.

Since the product is of a viscous nature, it is ideal for use on vertical or inclined surfaces.

KEM-2015 AP is not corrosive to most of metals such as Aluminum, Titanium, Cadmium plated steels etc. Do not use **KEM-2015 AP** on Magnesium and Magnesium alloys.

Advantages

- The most effective paint remover used where traditional paint removers have poor results.
- Non-flammable.
- Easily rinsed with cold water.
- Can be applied by brush or non-atomizing spray methods.
- Used as received. No mixing or dilution required.
- Used at room temperature.

Usage

KEM-2015 AP can be applied as received by brush or spray. Because it is thick it is ideal for vertical surfaces.

Allow **KEM-2015 AP** sufficient dwell time for thorough loosening or blistering of the paint. When paint is loose, thoroughly agitate all areas with a stiff bristle brush. The complete removal of the paint residues is accomplished with high pressure, high volume, cold water or with a steam cleaning machine.

Normally a coat of **KEM-2015 AP** is sufficient to remove more than one coating of paint.

Safety

KEM-2015 AP contains chlorinated hydrocarbons and phenolic bodies. Avoid contact with skin, eyes and clothing. Gloves, goggles, face shields are recommended when handling. For further information refer to Material Safety Data Sheet.

Packaging

KEM-2015 AP is available in 250 kg drums.

EUROCHEM S.A.

4 RAFAILIDOU St. 177 78 TAVROS, ATHENS, GREECE

TEL.: +30 210 48 36 321-7, FAX: +30 210 48 36 331-2

E-mail: eur98@otenet.gr - <http://www.eurochem.gr>, www.eurochemgr.com