

<u>KEM - 2040</u> (NON-PHENOLIC PAINT STRIPPER) MIL-PRF-25134 C

Description

KEM-2040 is a thickened, non phenolic aircraft paint stripper which meets the requirements of BOEING Document D6-17487 and MIL-PRF-25134 C.

Application

KEM-2040 is a viscous liquid developed to remove multiple coats of paint. It clings to vertical as well as the underside of horizontal surfaces.

KEM-2040 is specially designed to remove lacquer and enamel coating finishes from metal surfaces of aircraft or other surfaces.

KEM-2040 is even suitable for stripping various types of paints such as varnish, zinc chromate primer, epoxy, polyurethane, etc.

<u>Advantages</u>

- Safe to all metals.
- Very effective, normally removes more than one coating of paint.
- Non-flammable.
- Free of phenolics.
- Easily rinsed with cold water.
- Can be applied by brush or non-atomizing spray methods.
- Used as received. No mixing or dilution required.
- Used at room temperature.

<u>Usage</u>

KEM-2040 can be applied as received by brushing or spraying. Because of it is thick is ideal for vertical surfaces.

Allow KEM-2040 sufficient dwell time for thorough loosening or blistering of the paint. When paint is loose, thoroughly agitate all areas with a stiff bristle brush. The complete removal of the paint residues is accomplished with high pressure, high volume, cold water or with a steam cleaning machine.

Normally one coat of KEM-2040 is sufficient to remove more than one paint coating.

Where multicoat systems have to be removed, it may be necessary to use more than one application of KEM-2040.

Safety

KEM-2040 contains chlorinated solvents and chromates. Avoid contact with skin, eyes and clothing. Gloves, goggles, face shields are recommended when handling. For further information refer to Material Safety Data Sheet.

Packaging

KEM-2040 is available in 55 gallon drums.