



LECTROKLEEN - S

Description

LECTROKLEEN - S is a highly effective cleaning compound especially formulated to replace 1,1,1 Trichloroethane in all cleaning operations where a balanced evaporation rate solvent is required.

Application

Electric motors, electric equipment, panel boards, pumps, valves, machinery, starters, generators, connectors, fans and blowers, cables and wires, distributors, military aircraft, mechanical parts, motors, engines, etc.

Advantages

LECTROKLEEN - S is a product with a balanced evaporation rate and lasts at least twice as long ordinary solvent cleaners. High MAC rating and low toxicity make it an outstanding cleaner. Good cleaning and degreasing properties. Removes oil, grease, wax, dust, moisture, soil, etc. High dielectric constant (over 30.000 Volts).

Usage

LECTROKLEEN - S is used neat and may be applied by brushing dipping or non-atomizing spray. Allow LECTROKLEEN - S to completely evaporate leaving surface dry.

Specification

Appearance	: colorless liquid
Specific gravity	: 0,92 ± 0,02
Flash point	: > 60°C
Corrosive action	: none
pH	: neutral

Caution

LECTROKLEEN - S contains chlorinated solvents. Avoid contact with skin and eyes. Do not inhale vapors. Use in ventilated areas. For further information refer to M.S.D.S.

Packaging

LECTROKLEEN - S is offered in non-returnable 20 lt. pails and 210 lt. drums.

Note

When a fast evaporating product is required use our product LECTROKLEEN - D4 - FAST.