



PR – 2025 **(EPOXY & POLYURETHANE PAINT REMOVER)**

Description

PR-2025 is a very effective, thickened paint stripper, which meets the requirements of MIL-R-81294D Type I, II, III & IV, Class 1 (phenolic, chromate inhibited) and BOEING Document D6-17847.

Application

PR-2025 is especially designed for removing epoxy and polyurethane paints as well as other difficult to remove organic coatings from the metal surfaces of the aircrafts. It is safe for all type of metals.

Advantages

- Safe to all metals.
- Very effective, normally removes more than one coating of paint.
- Non-flammable.
- Easily rinsed with cold water.
- Can be applied by brush or non-atomizing spray methods.
- Used as received. No mixing or dilution required.
- Used at room temperature.

Usage

PR-2025 can be applied as received by brush or spray. Because it is thick it is ideal for vertical surfaces.

Allow **PR-2025** sufficient dwell time for thorough loosening or blistering of the paint. When paint is loose, thoroughly agitate all areas with a stiff bristle brush. The complete removal of the paint residues is accomplished with high pressure, high volume, cold water or with a steam cleaning machine.

Normally a coat of **PR-2025** is sufficient to remove more than one coating of paint.

Where multicoat systems have to be removed, it may be necessary to use more than one application of **PR-2025**.

Safety

PR-2025 contains chlorinated hydrocarbons and phenolic bodies. Avoid contact with skin, eyes and clothing. Gloves, goggles, face shields are recommended when handling. For further information refer to Material Safety Data Sheet.

Packaging

PR-2025 is available in 5 & 55 gallons.