



COAL & TAR REMOVER

Description

COAL & TAR REMOVER is a solvent emulsion cleaner with surfactants for fast effective cleaning.

Applications

COAL & TAR REMOVER is ideal for removing asphalt, tar, mineral oils and greases from machinery parts, diesel engine exteriors, compressors exteriors, tank tops, bulkheads, decks, bunker tanks etc. Also is suitable for engine rooms, decks and spot cleaning/degreasing of oil tanks.

Advantages

COAL & TAR REMOVER is safe for all metals, glass, plastic, wood and painted surfaces. Loosens and breaks up deposits, has a strong emulsifying action and it is easy to use. COAL & TAR REMOVER can be used as an all-purpose degreaser.

Usage

COAL & TAR REMOVER may be used neat or diluted with solvents or water in varying concentrations depending on the heaviness of the soil by soaking, spraying or combined with scrubbing.

Soaking: Parts are immersed in COAL & TAR REMOVER. Allow deposit to be broken up and loosened before removal. Then rinse off with water.

Spraying: Apply COAL & TAR REMOVER over all soiled areas. Allow time for COAL & TAR REMOVER to act, between 15-30 minutes, then rinse off by water hose.

Recirculation: Apply COAL & TAR REMOVER in proportion 8-10%. For better results heat the solution.

Scrubbing: Use COAL & TAR REMOVER neat and agitate by scrubbing where soiling is stubborn. Rinse off with water.

Butterworth or steam cleaning machines: Use concentration of 0,1 – 1% at the nozzle.

Caution

Avoid contact with skin and eyes. For further information refer to Material Safety Data Sheet (SDS).

Packaging

Nonreturnable 210 lt. drums and 30 lt. pails.